

U-2011

SEMI-AUTOMATIC SWING ARM


**STANDARD
MODEL**

FEATURES



INTERNATIONAL PATENTED
098 HELP ARM (RIGHT)



Adopt rugged & durable
one-piece casting jaws.




Adjustable pressing shovel
helps to press tyre with less
effort.




Standard configuration:
Bead pressing tool

PARAMETERS



10~21"
External clamping



12~24"
Internal clamping



<1000mm(39")
Max.wheel diameter



<355mm(14")
Max. wheel width

TECHNICAL DATA

Air supply pressure	8-10bar (116-145 psi)
Power supply	220-240V 50~60Hz (1ph)
Motor power	0.75 kw
Noise level	s75 dB
N/G weight	207/229 kg(455/504 lbs)
Package dimension	960*760*800mm(3.1* 2.5*2.6ft)



HELP ARM

INTERNATIONAL PATENTED RIGHT 098 HELP ARM



Simple 098 help arm device makes low profile tyre changing easier



OPTIONAL CONFIGURATION

Option 1 :
Barrel-type Tyre
Inflator Blaster



UB-TF1
Installed on
tyre changer

U-2011-TF1

Option 2:
Traditional quick
air booster



U-2011A

Option 3 :
Motorcycle
Adapter



Optional:
Barrel-type Tyre Inflator Blaster



UB-TF2
Individual
Type



UB-TFM
Mobile &
Individual Type